



Super-flexible coaxial feeder cable, helical corrugated copper for outer conductor and copper-clad aluminum wire for inner conductor, 1/4 in, LSZH jacket

General Specifications

Flexibility	Super-flexible
Jacket Color	Black
Performance Note	Attenuation guaranteed within the tolerance $\pm 10\%$
Structure Note	Dimension guaranteed within the tolerance $\pm 5\%$
Nominal Size	1/4 in

Material Specifications

Inner Conductor	Copper-Clad Aluminum Wire
Dielectric	Physical Foam Polyethylene
Outer Conductor	Helical Corrugated Copper Tube
Jacket	LSZH
Diameter of Inner Conductor	1.90 mm
Diameter of Dielectric	4.80 mm
Diameter of Outer Conductor	6.40 mm
Diameter of Jacket	7.40 mm

Electrical Specifications

Impedance	50 ohms ± 1 ohm
Maximum Available Frequency	20.4 GHz
Cut-off Frequency	25 GHz
Velocity Ratio	82%
Peak Power	8.2 kW
Insulation Resistance	3000 M Ω -km
DC Breakdown Voltage	1600 V
Nominal Capacitance	80 pF/m
Nominal Inductance	0.195 μ H/m

Attenuations

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.40	0.12	6.40
1	0.57	0.17	6.40
1.5	0.70	0.21	6.40
2	0.81	0.25	6.40
10	1.81	0.55	3.97
20	2.57	0.78	2.80
30	3.16	0.96	2.28
50	4.10	1.25	1.76
88	5.15	1.57	1.32
100	5.52	1.68	1.13
108	6.07	1.85	1.01
150	7.18	2.19	1.00
174	7.74	2.36	0.93
200	8.33	2.54	0.87
300	10.31	3.14	0.70
400	11.98	3.65	0.60
450	12.21	3.72	0.52
500	13.37	4.08	0.51
512	13.56	4.13	0.50
600	14.75	4.50	0.45
700	16.04	4.89	0.45
800	17.23	5.25	0.42
824	17.43	5.31	0.41
900	17.76	5.41	0.37
960	18.91	5.76	0.37
1000	19.41	5.92	0.37
1250	21.78	6.64	0.30
1500	24.06	7.33	0.28
1700	25.74	7.85	0.28
1800	26.08	7.95	0.25
2000	28.22	8.60	0.25
2100	28.91	8.81	0.24
2200	29.70	9.05	0.24
2400	31.42	9.58	0.21
3000	34.89	10.63	0.19
4000	41.39	12.62	0.17
6000	52.18	15.90	0.14
8000	61.78	18.83	0.12

Return Loss / VSWR

Frequency Band	VSWR	Return Loss (dB)	Tolerance
0.8-1.0GHz	1.15	23.1	5%
1.7-2.2GHz	1.15	23.1	5%
2.2-2.7GHz	1.15	23.1	5%
3.3-3.8GHz	1.22	20.1	5%
4.8-5.0GHz	1.22	20.1	5%

Mechanical Specifications

Bending Radius (Single)	≥12 mm
Bending Radius (Repeated)	≥25 mm
Number of Bending (Typical)	≤9
Tensile Strength	680N

Environmental Specifications

Installation Temperature	-20 °C to +55 °C
Operating Temperature	-20 °C to +85 °C
Storage Temperature	-25 °C to +85 °C

Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.