



Flexible coaxial feeder cable, ring corrugated copper for outer conductor and helical copper tube for inner conductor, 1-5/8 in, LSZH jacket

## General Specifications

Flexibility	Standard
Jacket Color	Black
Performance Note	Attenuation guaranteed within the tolerance $\pm 10\%$
Structure Note	Dimension guaranteed within the tolerance $\pm 5\%$
Nominal Size	1-5/8 in

## Material Specifications

Inner Conductor	Helical Copper Tube
Dielectric	Physical Foam Polyethylene
Outer Conductor	Ring Corrugated Copper Tube
Jacket	LSZH
Diameter of Inner Conductor	17.30 mm
Diameter of Dielectric	41.80 mm
Diameter of Outer Conductor	46.50 mm
Diameter of Jacket	49.80 mm

## Electrical Specifications

Impedance	50 ohms $\pm 1$ ohm
Maximum Available Frequency	2.5 GHz
Cut-off Frequency	3.0 GHz
Velocity Ratio	88%
Peak Power	310 kW
Insulation Resistance	3000 M $\Omega$ -km
DC Breakdown Voltage	15000 V
Nominal Capacitance	76 pF/m
Nominal Inductance	0.19 $\mu$ H/m

## Attenuations

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.044	0.013	247.00
1	0.062	0.019	175.00
1.5	0.076	0.023	142.00
2	0.088	0.027	123.00
10	0.200	0.061	54.30
20	0.286	0.087	38.10
30	0.371	0.113	30.90
50	0.460	0.140	23.60
88	0.621	0.189	17.50
100	0.664	0.202	16.40
108	0.692	0.211	15.70
150	0.826	0.252	13.20
174	0.895	0.273	12.20
200	0.966	0.294	11.30
300	1.208	0.368	9.01
400	1.535	0.468	7.67
450	1.683	0.513	7.00
500	1.782	0.543	6.76
512	1.832	0.558	6.67
600	1.881	0.573	6.09
700	1.970	0.600	5.57
800	2.149	0.655	5.15
824	2.257	0.688	5.06
900	2.475	0.754	4.68
960	2.584	0.788	4.60
1000	2.713	0.827	4.52
1250	2.772	0.845	3.95
1500	3.188	0.972	3.54
1700	3.515	1.071	3.28
1800	3.663	1.116	3.08
2000	3.822	1.165	2.96
2300	4.079	1.243	2.72
2500	4.386	1.337	2.58

## Return Loss / VSWR

Frequency Band	VSWR	Return Loss (dB)	Tolerance
0.4-0.5GHz	1.15	23.1	5%
0.8-1.0GHz	1.15	23.1	5%
1.7-2.2GHz	1.15	23.1	5%
2.2-2.5GHz	1.15	23.1	5%

## Mechanical Specifications

Bending Radius (Single)	≥280 mm
Bending Radius (Repeated)	≥500 mm
Number of Bending (Typical)	≤15
Tensile Strength	3000N

## Environmental Specifications

Installation Temperature	-20 °C to +55 °C
Operating Temperature	-20 °C to +85 °C
Storage Temperature	-25 °C to +85 °C

## Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.