



Radiating cable, slotted and corrugated copper tape for outer conductor and helical copper tube for inner conductor, foam PE dielectric, 1-5/8 in, FRNC jacket

General Specifications

Flexibility	Standard
Jacket Color	Black
Performance Note	Attenuation guaranteed within the tolerance $\pm 10\%$
Structure Note	Dimension guaranteed within the tolerance $\pm 5\%$
Nominal Size	1-5/8 in

Material Specifications

Inner Conductor	Helical Copper Tube
Dielectric	Foam PE
Outer Conductor	Slotted and Corrugated Copper Tape
Jacket	FRNC
Diameter of Inner Conductor	17.30 mm
Diameter of Dielectric	43.50 mm
Diameter of Outer Conductor	43.60 mm
Diameter of Jacket	49.50 mm

Electrical Specifications

Impedance	50 ohms ± 1 ohm
Maximum Available Frequency	1000 MHz
Stop Band	355-400 / 715-770 MHz
Velocity Ratio	89%
Peak Power	310 kW
Insulation Resistance	100,000 M Ω -km
DC Breakdown Voltage	8000 V
Nominal Capacitance	70 pF/m
Nominal Inductance	0.19 μ H/m

Attenuations

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Coupling Loss, 2m (dB, 50% / 95%)
75	0.70	0.21	69/81
100	0.80	0.24	62/74
150	0.90	0.27	70/81
350	1.50	0.46	73/83
450	1.70	0.52	69/79
800	2.50	0.76	62/68
900	2.70	0.82	62/66

Return Loss / VSWR

Frequency Band	VSWR	Return Loss (dB)	Tolerance
100-2650MHz	1.30	17.7	5%

Mechanical Specifications

Bending Radius (Single)	≥500 mm
Bending Radius (Repeated)	≥750 mm
Number of Bending (Typical)	≤15
Tensile Strength	2450N

Environmental Specifications

Installation Temperature	-20 °C to +55 °C
Operating Temperature	-20 °C to +85 °C
Storage Temperature	-25 °C to +85 °C

Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.