



4.3-10 male connector for 7/8 in flexible feeder cable, field installation with reliable connection.

General Specifications

| | |
|---------------------|---|
| Connector Type | Field installation |
| Connector Interface | 4.3-10 male |
| Suitable Cable | 7/8-inch feeder cable with standard flexibility |
| Mechanical Standard | IEC 61169-16 |

Electrical Specifications

| | |
|---------------------------|--|
| Impedance | 50 ohms |
| Frequency | DC - 6GHz |
| Return Loss | ≤ -26 dB@DC-3GHz ≤ -23 dB@3-4GHz ≤ -21 dB@4-6GHz |
| Insertion Loss | ≤ 0.05 dB |
| Insulation Resistance | 10 G Ω |
| Center Contact Resistance | ≤ 0.4 M Ω |
| Outer Contact Resistance | ≤ 1.5 M Ω |
| Working Voltage | 500 V |
| Power Handling | 1800 W@1GHz |
| Intermodulation, 900MHz | -161 dBc@2 \times 43dBm Typical -155 dBc@2 \times 43dBm Maximum |

Parts Material

| | |
|------------------------|----------------|
| Inner Conductor | Brass |
| Inner Conductor Socket | Tin bronze |
| Insulator | PTFE/TPX |
| Body & Outer Conductor | Brass |
| Gasket | Silicon rubber |
| Nut | Brass |

Surface Plating Treatment

| | |
|------------------------|--------------------------|
| Inner Conductor | Silver Ag3 plated |
| Inner Conductor Socket | Silver Ag3 plated |
| Body & Outer Conductor | Tri-metal CuSnZn3 plated |
| Nut | Nickel Ni3 plated |

Mechanical Specifications

| | |
|-------------------------------|---|
| Mating Cycles | ≥500 times |
| Coupling Nut Retention | ≥1000 N |
| Coupling Torque (Recommended) | ≥25 to 30 Nm |
| Proof Torque | ≤35 Nm |
| Mechanical Shock Test Method | MIL-STD-202, Method 213, Test Condition D |
| Vibration Test Method | MIL-STD-202, Method 204, Test Condition A |

Environmental Specifications

| | |
|--------------------------|----------------------------------|
| Installation Temperature | -20 °C to +55 °C |
| Operating Temperature | -40 °C to +85 °C |
| Storage Temperature | -45 °C to +85 °C |
| Relative Humidity | 5% - 95% |
| IP Rating | Mated IP68, 1m, 1.5hrs, 20 deg-C |

Regulatory Compliances

| | |
|---------------|-----------|
| ISO 9001:2015 | Compliant |
| ROHS | Compliant |
| China RoHS | Compliant |
| UK RoHS | Compliant |
| REACH | Compliant |
| EU/CE | Compliant |

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.