



Small cell antenna, sector antenna, XXPol, 1710-2700MHz / 3400-3600MHz, typical gain 13dBi/13dBi, HBW 30°/30°, 0° fixed electrical down tilt, without integrated combiner.

## General Specifications

Product Type	Small cell antenna, sector antenna
Polarization	XX-Pol
Integrated RET	N/A
Integrated Combiner	N/A
Frequency Band	1710-2700 / 3400-3600MHz
Ports	4-port
Connector Interface	4.3-10 female
Mounting	Wall and pole mounting

## Electrical Specifications

Frequency Band (MHz)	1710-2700	3400-3600
Gain (dBi)	13.0±1.0	13.0±1.0
Horizontal Beamwidth	30±6°	30±6°
Vertical Beamwidth	30±6°	30±6°
Front-to-back Ratio	≥22 dB	≥20 dB
Sidelobe Suppression	≥17 dB	≥17 dB
Isolation Intra-system	≥25 dB	≥25 dB
VSWR	≤1.8	
Polarization	±45°	
Power Handling	200W	
Intermodulation, 2×43dBm	≤-150dBc	
Impedance	50 ohms	

## Mechanical Specifications


Antenna Dimension	620×320×105 mm
Packing Dimension	870×410×250 mm
Antenna Weight	7.0 kg
Connectors Type	4.3-10 female

Radome Material	UPVC
Radome Color	Gray
Mechanical Tilt	0-10°
Mounting	Wall and pole mounting
Mounting Diameter Range	φ50-115 mm
Packing	1pcs in box


## Environmental Specifications

Operating Temperature	-40 °C to +65 °C
Storage Temperature	-45 °C to +85 °C
Relative Humidity	5% - 95%
Max. Wind Velocity	216 km/h
Application	Outdoor

## Patterns



1710-2690 MHz



3400-3600 MHz

## Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.