



Small cell antenna, sector antenna, XXXXPol, 1710-2700MHz×2 / 3300-3800MHz×2, typical gain 11dBi/12dBi, HBW 65°/65°, 0° fixed electrical down tilt, with integrated combiner.

General Specifications

Product Type	Small cell antenna, sector antenna
Polarization	XXXX-Pol
Integrated RET	N/A
Integrated Combiner	4
Frequency Band	1710-2700 / 3300-3800MHz
Ports	4-port
Connector Interface	4.3-10 female
Mounting	Wall and pole mounting

Electrical Specifications

Frequency Band (MHz)	1710-2700	3300-3800
Gain (dBi)	11.0±1.0	12.0±1.0
Horizontal Beamwidth	65±6°	60±6°
Vertical Beamwidth	35±6°	30±6°
Front-to-back Ratio	≥22 dB	≥20 dB
Sidelobe Suppression	≥17 dB	≥17 dB
Isolation Intra-system	≥25 dB	≥25 dB
VSWR	≤1.5	
Polarization	±45°	
Power Handling	200W	
Intermodulation, 2×43dBm	≤-150dBc	
Impedance	50 ohms	

Mechanical Specifications


Antenna Dimension	335×320×80 mm
Packing Dimension	565×405×170 mm
Antenna Weight	4.0 kg
Connectors Type	4.3-10 female

Radome Material	UPVC
Radome Color	Gray
Mechanical Tilt	0-10°
Mounting	Wall and pole mounting
Mounting Diameter Range	φ50-115 mm
Packing	1pcs in box


Environmental Specifications

Operating Temperature	-40 °C to +65 °C
Storage Temperature	-45 °C to +85 °C
Relative Humidity	5% - 95%
Max. Wind Velocity	216 km/h
Application	Outdoor

Patterns



1710-2690 MHz



3300-3800 MHz

Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.