



The high-capacity stadium antenna covers 1710-2700MHz frequency band with N-female connector interface. Benefitted by the excellent pattern performance and 4×4 MIMO application, it is widely used for in-building mobile coverages.

General Specifications

Product Type	Stadium Panel Antenna
Frequency Band	1710-2700MHz
Ports	4-port MIMO
Connector Interface	N female
Mounting	Wall and pole mounting

Electrical Specifications

Frequency Band (MHz)	1710-2170	2300-2700
Gain (dBi)	12.0±0.5	13.0±0.5
Horizontal Beamwidth	35±15°	30±15°
Vertical Beamwidth	35±15°	30±15°
Port Isolation	≥25dB	
VSWR	≤1.8	
Polarization	±45°	
Power Handling	100W	
Intermodulation, 2×43dBm	≤-153dBc	
Impedance	50 ohms	

Mechanical Specifications

Dimension	756×756×118 mm
Weight	12 kg
Connectors Type	N female
Radome Material	ABS
Radome Color	White
Mounting	Wall and pole mounting
Packing	1pcs in box


Environmental Specifications

Installation Temperature	-10 °C to +55 °C
Operating Temperature	-20 °C to +65 °C
Storage Temperature	-45 °C to +85 °C
Relative Humidity	5% - 95%
Application	Indoor and outdoor

Patterns

1710-2170 MHz

2300-2700 MHz



Horizontal Pattern

Vertical Pattern

Horizontal Pattern

Vertical Pattern

Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.