



The hybrid coupler is widely used in the in-building DAS deployment to combine and mix the same-band systems. The product is designed with wide frequency band, customized connector interface, high power handling, low PIM performance and high reliability for indoor and outdoor coverage applications.

General Specifications

| | |
|---------------------|--------------------|
| Product Type | RF Hybrid Coupler |
| Frequency Band | 694-3800 MHz |
| Port Number | 4-input / 4-output |
| Connector Interface | 7/16 DIN female |

Electrical Specifications

| | |
|--------------------------|--------------|
| Frequency Band (MHz) | 694-3800 MHz |
| Return Loss | ≤ -18 dB |
| VSWR | ≤ 1.3 |
| Insertion Loss | ≤ 0.3 dB |
| Distribution Loss | Nominal 6 dB |
| Distribution Loss Ripple | ± 0.8 dB |
| Isolation | ≥ 23 dB |
| Power Handling | 500W |
| Intermodulation, 2×43dBm | ≤ -155dBc |
| Impedance | 50 ohms |

Material Specifications

| | | |
|-----------|-----------------------------------|-------------------|
| Cavity | Cavity Enclosure | Aluminum alloy |
| | Cavity Outer Surface Treatment | Black painting |
| | Cavity Inner Surface Treatment | Cu3Ag1 |
| | Inner Conductor | Aluminum alloy |
| Connector | Inner Conductor Surface Treatment | Ag1 |
| | Outer Conductor | Brass |
| | Outer Conductor Surface Treatment | Tri-metal CuSnZn3 |
| | Inner Conductor | Brass |
| | Inner Conductor Surface Treatment | Ag1 |
| | Insulator | PTFE/TPX |
| | Gasket | Silicon rubber |


Mechanical Specifications

| | |
|-----------------|---------------------------------------------------|
| Dimension | 216x140x63 mm (Excluding connectors and brackets) |
| Weight | 4.5 kg |
| Connectors Type | 7/16 DIN female |
| Mounting | Wall or rack |
| Packing | 1pcs in box |

Environmental Specifications

| | |
|-----------------------|--------------------------|
| Operating Temperature | -40 °C to +65 °C |
| Storage Temperature | -45 °C to +85 °C |
| Relative Humidity | 5% - 95% |
| Application | IP65, indoor and outdoor |

Outline Drawing



Regulatory Compliances

| | |
|---------------|-----------|
| ISO 9001:2015 | Compliant |
| ROHS | Compliant |
| China RoHS | Compliant |
| UK RoHS | Compliant |
| REACH | Compliant |
| EU/CE | Compliant |

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, but nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.