



Multi-band RF combiner, triplexer, 612-960MHz/1695-2700MHz/3300-4200MHz combination, single unit 3-input / 1-output, 7/16 DIN female, -155dBc, DC bypass for all ports.

General Specifications

Product Type Multi-Band Combiner

Channel Number 3-way Triplexer

Frequency Band 612-960MHz | 1695-2700MHz | 3300-4200MHz

Input / Output 3-input and 1-output

Structure Single Unit
Connector Interface 7/16 DIN female

Electrical Specifications

Frequency Band (MHz) 612-960 1695-2700 3300-4200 Return Loss ≤-20.8 dB ≤-20.8 dB ≤-20.8 dB **VSWR** ≤1.20 ≤1.20 ≤1.20 **Insertion Loss** ≤0.5 dB ≤0.5 dB ≤0.5 dB Isolation ≥50 dB ≥50 dB ≥50 dB

Impedance 50 ohms

Material Specifications

Cavity Cavity Enclosure Aluminum alloy
Cavity Outer Surface Treatment Powder coating

Cavity Inner Surface Treatment Cu3Ag1

Inner Conductor Aluminum alloy

Inner Conductor Surface Treatment Ag1

Connector Outer Conductor Brass

Outer Conductor Surface Treatment Tri-metal CuSnZn3

Inner Conductor Brass

Inner Conductor Surface Treatment Aq1

Insulator PTFE/TPX
Gasket Silicon rubber



Mechanical Specifications

Dimension 165×154×52 (mm, excluding connectors and brackets)

Weight 3.5 kg

Connectors Type 7/16 DIN female
Mounting Wall and pole
Packing 1pcs in box

Environmental Specifications


Operating Temperature -40 °C to +65 °C

Storage Temperature -45 °C to +85 °C

Relative Humidity 5% - 95%

Application IP67

Outline Drawing



Regulatory Compliances

ISO 9001:2015 Compliant
ROHS Compliant
China RoHS Compliant
UK RoHS Compliant
REACH Compliant
EU/CE Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.