



Multi-band RF combiner, quadplexer, 617-894MHz and 1710-1755/2110-2155MHz and 1850-1990MHz and 2300-2700MHz combination, single unit 4-input / 1-output, 4.3-10 female, -155dBc, DC bypass for all ports.

General Specifications

Product Type	Multi-Band Combiner
Channel Number	4-way Quadplexer
Frequency Band	617-894MHz 1710-1755/2110-2155MHz 1850-1990MHz 2300-2700MHz
Input / Output	4-input and 1-output
Structure	Single Unit
Connector Interface	4.3-10 female

Electrical Specifications

Frequency Band (MHz)	617-894	1710-1755/2110-2155	1850-1990	2300-2700
Return Loss	≤-20.8 dB	≤-20.8 dB	≤-20.8 dB	≤-20.8 dB
VSWR	≤1.20	≤1.20	≤1.20	≤1.20
Insertion Loss	≤0.5 dB	≤0.5 dB	≤0.5 dB	≤0.5 dB
Isolation	≥50 dB	≥50 dB	≥50 dB	≥50 dB
Intermodulation (3rd order)	≤-155dBc@2×43dBm			
DC Bypass	DC bypass for all ports			
Power Handling	200 watts per port			
Impedance	50 ohms			

Material Specifications

Cavity	Cavity Enclosure	Aluminum alloy
	Cavity Outer Surface Treatment	Powder coating
	Cavity Inner Surface Treatment	Cu3Ag1
	Inner Conductor	Aluminum alloy
	Inner Conductor Surface Treatment	Ag1
Connector	Outer Conductor	Brass
	Outer Conductor Surface Treatment	Tri-metal CuSnZn3
	Inner Conductor	Brass
	Inner Conductor Surface Treatment	Ag1
	Insulator	PTFE/TPX
Gasket	Silicon rubber	


Mechanical Specifications

Dimension	268×177×54 (mm, excluding connectors and brackets)
Weight	4.5 kg
Connectors Type	7/16 DIN female
Mounting	Wall and pole
Packing	1 pcs in box

Environmental Specifications

Operating Temperature	-40 °C to +65 °C
Storage Temperature	-45 °C to +85 °C
Relative Humidity	5% - 95%
Application	IP67

Outline Drawing



Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.