



Multi-band RF combiner, quadplexer, 694-880MHz/890-960MHz/1710-1880MHz/1920-2700MHz combination, single unit 4-input / 1-output, 7/16 DIN female, -155dBc, DC bypass for all ports.

## General Specifications

Product Type	Multi-Band Combiner
Channel Number	4-way Quadplexer
Frequency Band	694-880MHz   890-960MHz   1710-1880MHz   1920-2700MHz
Input / Output	4-input and 1-output
Structure	Single Unit
Connector Interface	7/16 DIN female

## Electrical Specifications

Frequency Band (MHz)	694-880	890-960	1710-1880	1920-2700
Return Loss	≤-20.8 dB	≤-20.8 dB	≤-20.8 dB	≤-20.8 dB
VSWR	≤1.20	≤1.20	≤1.20	≤1.20
Insertion Loss	≤0.8 dB	≤0.8 dB	≤0.6 dB	≤0.6 dB
Isolation	≥50 dB	≥50 dB	≥50 dB	≥50 dB
Intermodulation (3rd order)	≤-155dBc@2×43dBm			
DC Bypass	DC bypass for all ports			
Power Handling	200 watts per port			
Impedance	50 ohms			

## Material Specifications

Cavity	Cavity Enclosure	Aluminum alloy
	Cavity Outer Surface Treatment	Powder coating
	Cavity Inner Surface Treatment	Cu3Ag1
	Inner Conductor	Aluminum alloy
Connector	Inner Conductor Surface Treatment	Ag1
	Outer Conductor	Brass
	Outer Conductor Surface Treatment	Tri-metal CuSnZn3
	Inner Conductor	Brass
	Inner Conductor Surface Treatment	Ag1
	Insulator	PTFE/TPX
	Gasket	Silicon rubber


## Mechanical Specifications

Dimension	264×200×54 (mm, excluding connectors and brackets)
Weight	4.5 kg
Connectors Type	7/16 DIN female
Mounting	Wall and pole
Packing	1 pcs in box

## Environmental Specifications

Operating Temperature	-40 °C to +65 °C
Storage Temperature	-45 °C to +85 °C
Relative Humidity	5% - 95%
Application	IP67

## Outline Drawing



## Regulatory Compliances

ISO 9001:2015	Compliant
ROHS	Compliant
China RoHS	Compliant
UK RoHS	Compliant
REACH	Compliant
EU/CE	Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.