



Same band combiner, diplexer, 900MHz same band combination. 880.1-889.9/925.1-934.1MHz and 902.5-914.9/947.5-959.9MHz, double unit 4-input / 2-output, 4.3-10 female, -155dBc, DC bypass for all ports, 19-inch cabinet installation.

General Specifications

Product Type Same Band Combiner

Channel Number 2-way Diplexer

Frequency Band 880.1-889.9/925.1-934.1MHz | 902.5-914.9/947.5-959.9MHz

Input / Output 4-input and 2-output

Structure Double Unit
Connector Interface 4.3-10 female

Electrical Specifications

Frequency Band (MHz) 880.1-889.9/925.1-934.1 902.5-914.9/947.5-959.9

Return Loss ≤-20.8 dB ≤-20.8 dB VSWR ≤1.20 ≤1.20 Insertion Loss ≤1.2 dB ≤1.2 dB ≥50 dB ≥50 dB

Intermodulation (3rd order) ≤-155dBc@2×43dBm

DC Bypass DC bypass for all ports

Power Handling 200 watts per port

Impedance 50 ohms

Material Specifications

Cavity Cavity Enclosure Aluminum alloy

Cavity Outer Surface Treatment Painting
Cavity Inner Surface Treatment Cu3Ag1

Inner Conductor Aluminum alloy

Inner Conductor Surface Treatment Ag1

Connector Outer Conductor Brass

Outer Conductor Surface Treatment Tri-metal CuSnZn3

Inner Conductor Brass
Inner Conductor Surface Treatment Aq1

Insulator PTFE/TPX
Gasket Silicon rubber



Mechanical Specifications

Height 2U Weight 4 kg

Connectors Type 4.3-10 female
Mounting 19-inch Rack
Packing 1pcs in box

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+65 \,^{\circ}\text{C}$ Storage Temperature $-45 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$

Relative Humidity 5% - 95% Application Indoor

Regulatory Compliances

ISO 9001:2015 Compliant
ROHS Compliant
China RoHS Compliant
UK RoHS Compliant
REACH Compliant
EU/CE Compliant

In the effort to improve our products, we reserve the right to make changes judged to be necessary. While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. The information contained in this document is subject to change without notice.